



5,000 lb x 1 lb
10,000 lb x 2 lb



- NTEP APPROVED CLASS III
- 4 X 4 FT OR 5 X 5 FT ALLOY STEEL PLATFORM
- BI-DIRECTIONAL RS232 INTERFACE
- EASY TO READ BACKLIT LED DISPLAY
- NET / GROSS, PRE-TARE, ANIMAL HOLD
- READS IN LB OR KG



Class III

PART NUMBER	TITAN F - 5K	TITAN F - 10K	TITAN F - 55 5K	TITAN F - 55 10K
Capacity	5,000 lb	10,000 lb	5,000 lb	10,000 lb
Readability	1 lb	2 lb	1 lb	2 lb
Platform Size	4' x 4'	4' x 4'	5' x 5'	5' x 5'
Weighing Units	lb, kg			
Functions	net / gross, pre-tare, animal hold, accumulation			
Power Source	External power adapter (supplied)			
Connectivity	RS232 bi-directional serial printer output			
Calibration	Via keyboard (internal adjust switch)			
Loadcell Excitation	5V DC \pm 5% 60 mA			
Internal Resolution	2,000,000 Counts maximum			
Display Resolution	5,000 NTEP			
Display	1 in high backlit display			
Operating Environment	32° F ~ 104° F / 0° C ~ 40° C			
Construction	Alloy steel base, w/ steel indicator w/ stainless steel U-shaped bracket			
Net Weight	250 lb / 114 kg		320 lb / 145 kg	
Shipping Weight	285 lb / 130 kg		350 lb / 159 kg	
Approvals	Base: NTEP CoC #10-081, Indicator: 12-004			
Options	Ramp, Scoreboards: 3", 5", 8" High Display. Call for details.			