




Made in Democratic Taiwan 



75 lb x 0.005 lb
150 lb x 0.01 lb
300 lb x 0.02 lb
750 lb x 0.05 lb



- WILL DRIVE 10 X 350 OHM OR 20 X 700 OHM LOAD CELLS
- ALIBI MEMORY STORES 130,000 + TRANSACTIONS FULL
- NUMERIC & FUNCTIONS KEYBOARD
- COUNTING RESOLUTION 1.2 MILLION
- MANAGEMENT CAPABILITIES
- MULTIPLE DATA COLLECTION
- OPTIONAL WHEEL KIT
- TRI-COLOR DISPLAY
- REAL TIME CLOCK
- 100 PLU'S

PART NUMBER	PSCII-AB-75	PSCII-AB-150	PSCII-AB-300	PSCII-AF-150	PSCII-AF-300	PSCII-AF-750	PSCII-AL-300	PSCII-AL-750
Capacity	75 lb	150 lb	300 lb	150 lb	300 lb	750 lb	300 lb	750 lb
Readability	0.005 lb	0.01 lb	0.02lb	0.01 lb	0.02 lb	0.05 lb	0.02 lb	0.05 lb
Divisions	30,000							
Weighing Units	lb, kg							
Functions	Counting, Statistics, Accumulation, Data Management							
Repeatability & Linearity	+ / - one division							
Tare Range	To capacity by subtraction							
Power Source	Built-in rechargeable battery or external power adapter (included)							
Indicator Construction	ABS							
Platform Construction	Stainless steel platform cover, cast aluminum base							
Display	Tri-color backlit LCD display							
Connectivity	RS232 Male & Female interfaces, 25 Pin relay port External input port							
Platform Size (W x D x H)	13 x 17.7 x 3.5 in / 330 x 450 x 89 mm			16.5 x 20.5 x 4.5 in / 420 x 520 x 120 mm			19.7 x 23.6 x 4.5 in / 500 x 600 x 120 mm	
Overall Dimensions (W x D x H)	13x 20.7 x 28.3 in / 330 x 450 x 720 mm			16.5 x 23.5 x 33.9 in / 420 x 520 x 860 mm			19.7 x 25.5 x 33.9 in / 500 x 647 x 860 mm	
Temperature Range	10°~ 40° C non condensing R.H. ≤ 85%							
Net Weight	25.8 lb / 11.7 kg			42.2 lb / 19.2 kg			56 lb / 25.4 kg	
Shipping Weight	29 lb / 13.2 kg			46 lb / 20.8 kg			63 lb / 28.4 kg	
Options	Ticket Printer, Label Printer, Wheel Kit, Secondary Weighing Platform Input, Stainless Steel U Shaped Bracket, Wireless Connection Wifi, Bluetooth 2.0 / 4.0 BLE							

FEATURES
Supports Single, Dual Range & Dual Interval operations
All Current Operation Results Output in Database Format for Data Management, Processing & Analysis
100 x PLU's per Each Platform (P1, P2 & P1+P2 Together)
Configurable Keypad, Check & System Buzzer
Real Time Clock
Alibi Memory to Store 130,000 Plus Transactions
Counting Resolution / Platform - 1.2 Million
Manual, Preset, Repetitive & Continuous Tare Operation
Continuous Tare w/ Configurable Delay Time Before Tare Action
Full Numeric & Functions Keyboard
Multi Search Criteria for Report Generation
Selectable Portrait / Landscape Ticket Printout Format
Customer & Product Code & Description Support Numbers, Alphabets & Selected Symbols
User Programmable & 10 x built-in Predefined Continuous / Interval Output Protocol
Check Result Control for Accumulation, Data Printout & Data Output
Supports Product Expiry Duration Input & Output
Machine ID, Machine Group & Operator Number
Daily, Monthly, Specific Period Report Output
Supports Customer & Product Code & Description Input
Supports Inquiry, Setting & Execution Comamands from a PC
10 x Quick PLU's for Unit Weight, Quantity Check Limits, Weight Check Limits, Pre-Set Tare, Customer & Product Code Description