



Made in Democratic Taiwan



30 lb x 0.01 lb
60 lb x 0.02 lb
150 lb x 0.05 lb
300 lb x 0.1 lb



Standard Configuration

Optional Pillar

Upgraded Transport Case

Portability Options

- CLASS III NTEP & MEASUREMENT CANADA
- VERSATILE & ECONOMICAL
- LARGE BACKLIT DISPLAY
- READS IN: KG, LB, ACCUMULATION
- LIGHTWEIGHT & PORTABLE
- OPTIONAL STAINLESS STEEL PILLAR



Class III

PART NUMBER	APM-15	APM-30	APM-60	APM-150
Capacity	15kg / 30 lb	30kg / 60 lb	60 kg / 150 lb	150 kg / 300 lb
Readability	0.005 kg / 0.01 lb	0.01 kg / 0.02 lb	0.02 kg / 0.05 lb	0.05 kg / 0.1 lb
Divisions	3,000			
Stabilization Time (seconds)	< 1.5			
Weighing Units	kg,lb, accumulation			
Tare Range	4.995 kg	9.99 kg	19.98 kg	49.95 kg
Power Source	Built-in rechargeable battery or external power adapter (included)			
Construction	Stainless steel pan, ABS housing			
Display	1 inch / 25.4 mm wide viewing angle backlit LCD			
Platform Size (W x D x H)	11 x 13 x 4.13 inches / 280 x 330 x 105 mm			
Overall Dimensions (W x D x H)	Platform mounted indicator: 11 x 16.5 x 4.1 inches / 280 x 420 x 105 mm w/ Pillar: 11 x 13 x 24.8 inches / 280 x 330 x 630 mm			
Operating Environment	32° F to 104° F non condensing R.H. ≤ 85%			
Net Weight	13.4 lb / 6.1 kg			
Shipping Weight	16 lb / 7.3 kg			
Options	Stainless Steel Pillar, Oxyweigher Transport Kit, Traveler Transport Case, Upgraded Transport Case			
Approvals	NTEP CoC #03-055, Measurement Canada Approval #AM-5544			

FEATURES	BENEFITS
Large LCD display w/ backlight	Gives excellent readability in sunlight, ideal for outdoor use
Heavy duty construction	Will withstand harsh industrial operation
Light weight	Ideal for portability, only 13.4 lb
Built-in rechargeable battery or external power adapter	Portability - battery lasts a minimum of 150 hours (w/out backlight)
Reads in kg & lb	Flexibility of operation
Zero Tracking	Ensures you always start weighing at zero
Automatic power save	Conserves battery power
Low battery indicator	Alerts you to charge the battery, saving down time
Easy calibration function	Ensures accuracy
Adjustable feet	Balance remains level for accurate results on uneven working surfaces - Anti-slip
Wide angle LCD display	Can be seen from a wide viewing range in sunshine, ideal for outdoor use
Optional auto tare function	Allows the first article on the platter to be automatically tared.