




Made in Democratic Taiwan



- CLASS III NTEP & MEASUREMENT CANADA
- COMPATIBLE W/ ANY BASE
- READS IN LB, KG, G, OZ
- 2" HIGH BACKLIT LCD DISPLAY
- OPTIONAL BI-DIRECTIONAL RS232
- WILL DRIVE 4 X 350 Ω LOAD CELLS



Class III

PART NUMBER	V-FS
Divisions	Up to 10,000 NTEP / 120,000 Non-NTEP
Weighing Units	lb, kg, g, oz only
Functions	Net / Gross, Accumulation
Tare Range	100% Subtractive
Power Source	External AC power adapter (included), rechargeable battery
Construction	IP 67 Stainless Steel Washdown
Display	2 inch high bright backlit LCD display
Connectivity	Optional Bi-Directional RS232 Interface
Net Weight	5.7 lb / 2.6 kg
Shipping Weight	7.5 lb / 3.4 kg
NEMA / IP Rating	NEMA 4X / IP 67
Options	Bi-Directional RS232 Interface, Printer
Approvals	NTEP CoC# 17-145, Measurement Canada Approval# AM-6092

FEATURES	BENEFITS
Large backlit display	Can be easily read in less than ideal conditions
Adjustable weighing speed filters	Allows you to adjust for operational & environmental conditions
Automatic Zero tracking	Ensures that you always start weighing at zero
Built-in rechargeable battery or external power adapter	Portability (battery lasts approximately 150 hours)
Automatic power save	Conserves battery power
Low battery indicator	Alerts you to charge the battery, saving downtime
RS232 Interface (Optional)	Allows for easy maintaining of records

